



PROCELERANT Z500

85mm x 70mm COM based on Intel® ATOM™ Processor

FEATURE SUMMARY

- 1.6GHz and 1.1GHz Intel ATOM processor
- 85mm x 70mm
- Up to 2GB DDR2 memory down
- Type 2 COM Express pinout
- Gigabit Ethernet and SATA port option
- Onboard microSD Socket

PRODUCT DESCRIPTION

RadiSys Procelerant™ Z500 COM Module is the innovative combination of Intel's low power 1.6GHz ATOM processor on a 85mm x 70mm standardized pin-out COM module. The ATOM processor delivers unprecedented performance and ultra low power in the smallest COM footprint possible that is compatible with a Type 2 COM Express pin out. The Procelerant Z500 delivers powerful performance with sub-5watt power dissipation. Along with up to 1GB memory down, a microSD socket, gigabit Ethernet, extended voltage range and smart battery support to make it ideal for battery powered handheld or mobile applications.

MICRO-SIZED COM

The Procelerant Z500 is the new 85mm x 70mm sized COM module that uses the COM Express Type 2 pin-out while optimizing on-board memory. The Procelerant Z500 provides 1GB of memory to alleviate memory bottlenecks when used with Intel's performance low power ATOM processors. The COM Express Type 2 connector specifies the connector for high speed serial differential signaling technologies such as PCI Express, Serial ATA, USB 2.0, LVDS, and Serial DVO while retaining some legacy support to ease migration from existing modular designs.

The Procelerant Z500 enables OEMs of handheld battery powered applications to start designing at the same time as processor release, saving months of development time and resources. OEM focus can remain on core competencies such as software and application development rather than high speed circuit design. Planned feature changes, demand fluctuations and performance upgrades can be handled without product re-designs using the The Procelerant Z500 COM Module. The Procelerant Z500 COM modules can reduce service repair inventories, and simplify upgrades, contributing to the success of the product over its lifetime.

DESIGN SERVICES BY THE COM EXPERTS AT RADISYS

OEMs can depend on RadiSys to support their design at every stage, whether it is carrier board design or services such as schematic reviews, debug assistance and custom BIOS generation. Carrier design tools such as the Carrier Design Guide, carrier schematics and Gerber files are available for customers committed to using RadiSys Procelerant CE processor modules. Carrier design consulting and debug services are also available to support OEM product development at any stage. Ask your RadiSys Sales Manager for more information.

Procelerant Z500 Specifications

Physical	Dimensions	85mm x 70mm	
	Compatibility	Utilizes PICMG COM Express R1.0 Type 2 pin-out	
Environment	Cooling	Forced air	Class EAC1 as defined in the ANSI/VITA 47-2005
		Conduction	Class ECC1 as defined in the ANSI/VITA 47-2005
Temperature	Operating	Ambient, up to +1800m: 0°C – 60°C, derated 2°C per 300m over 1800m	
	Non-operating	-40°C – 85°C	
Shock	Operating	50g, 11 millisecond, trapezoidal	
	Non-Operating/Unpacked	50g, 11ms, trapezoidal	
	Transportation/Packaged	Fictured assembly: 50G, 17.4 ms trapezoidal pulse Drop test, 10-up bulk packaging, 30in free-fall, one drop each of six faces	
Vibration	Operating	Random 5Hz to 2KHz, 12.07 grms, 1hr in each of 3 axes 5 – 40Hz 0.04 g2/Hz 40 – 100Hz 0.04 g2/Hz ramping up to 0.1g2/Hz (3dB/oct) 100Hz-1000Hz 0.1 g2/Hz 1000Hz-2000Hz: 0.1g2/Hz ramping down to 0.025g2/Hz (6dB/oct)	
	Non-Operating/Storage	Random 5Hz to 2KHz, 12.07 grms, 1hr in each of 3 axes 5 – 40Hz 0.04 g2/Hz 40 – 100Hz 0.04 g2/Hz ramping up to 0.1g2/Hz (3dB/oct) 100Hz-1000Hz 0.1 g2/Hz 1000Hz-2000Hz: 0.1g2/Hz ramping down to 0.025g2/Hz (6dB/oct) 5-500 Hz swept sine, 2.5g (0-p), 25.4mm(p-p) MAX displacement, 5 min dwell at 3 resonances in each of 3 axes.	
Humidity	Operating	5% to 95% non-condensing. 95%RH@30C, linear derating to 25%RH@70C*	
	Non-Operating/Storage	5% to 95% non-condensing	
Altitude	Operating	To 15,000ft (4570m) Up to 2300m (7500 ft), 0 to 60C Or Up to 2300m (7500 ft), -40C to +85C Derated -1.1 C per 305 m (1000 ft) above 2300 m (7500 ft)	
	Non-Operating/Storage	To 40,000ft (12000m)	
Regulatory	Safety	UL60950-1, EN60950-1, IEC60950-1	
		RoHS at time of production	
	EMC	EN55022, EN55024, and FCC Part 15, Subpart B, Class B	
Warranty	Standard	Two years, parts only	

MODULE SPECIFICATIONS:

Pinout	Type 2 COM Express Compatible		
Processor	Intel® Atom™ Processor Z530: 1.60GHz, 512K cache, 533MHz FSB Intel® Atom™ Processor Z510: 1.10GHz, 512K cache, 400MHz FSB		
Chipset	Intel System Controller Hub US15W		
Memory	Type	Eight (8) 400/533 DDR2 memory devices	
	Capacity	Up to 2GB memory	
Flash	4MB SPI ROM		

Video	US15W Integrated Graphics	<p>Single channel LVDS interface with 18-bit or 24-bit format</p> <ul style="list-style-type: none"> • Support resolutions up to 1366x768 pixels at 85Hz • Integrated PWM interface for LCD backlight inverter control <hr/> <p>One SDVO interface</p> <ul style="list-style-type: none"> • Supports resolutions up to 1280x1024 pixels at 85Hz
Networking		Optional 10/100/1000 Base-T, requires one x1 PCI Express lane
Audio		<p>High Definition Audio</p> <hr/> <p>Speaker Out</p>
Storage	SATA	Optional SATA interfaces capable of supporting one SATA device, requires one x1 PCI Express lane Supports both 1.5 and 3.0 Gbps operation
	IDE	One IDE interface capable of supporting two Ultra ATA/100 devices
	SDIO	MicroSD socket
PCI Express		Two x1 PCI Express link expansion ports, without Ethernet or SATA option
USB		Eight USB 2.0 expansion ports
LPC		One LPC interface
Power		+12 power rail, validated over 9V to 16.8V range
Power Management		ACPI 3.0 supporting states S0, S3, S4, S5, G3, and C0, C1, C2, C3, C4/C4E, C6
Miscellaneous		<p>One SMBus</p> <hr/> <p>One I2C bus</p> <hr/> <p>Eight GPIO (four GPI and four GPO)</p>
BIOS		General Software
Operating System		<p>Windows XP Embedded</p> <hr/> <p>Windows XP Professional</p> <hr/> <p>Windows Vista Ultimate Edition</p> <hr/> <p>Windows Vista Embedded Edition, as available</p> <hr/> <p>Windows CE 6.0</p> <hr/> <p>Red Hat Linux</p>

Ordering Information

Toll-Free: 800-950-0044

Phone: 503-615-1100

Support: 866-385-6167

Module Order Codes:

CEUS15-Z53-1GBL0: Type 2, 1.6 GHz ATOM Z530, 1GB, LAN, Computer

CEUS15-Z53-1GB0S: Type 2, 1.6 GHz ATOM Z530, 1GB, SATA Computer

CEUS15-Z51-512L0: Type 2, 1.1 GHz ATOM C510, 512MB LAN, Computer

Supporting Products:

CR200-PCIE16: Type 2, ATX Development Carrier

CEUS15-HSP: Z500 Heatspreader Assembly

Contact Information

www.radisys.com

info@radisys.com

Channels and other locations

Corporate Headquarters

5445 NE Dawson Creek Dr.

Hillsboro, OR 97124 USA

Phone: 503-615-1100

Fax: 503-615-1121

Toll-Free: 800-950-0044

Support: 866-385-6167

EMEA: +49 811 555457-0

China: 86.21.50804062

*2008 RadiSys Corporation. RadiSys is a registered trademark of RadiSys Corporation. Convidia, Microware and OS-9 are registered trademarks of RadiSys Corporation. Promentum, and Procelerant are trademarks of RadiSys Corporation. *All other trademarks are the properties of their respective owners. All specifications within this document are subject to change without notice.*