



AC Axial Fans

NMB offers a comprehensive line of more than 100 axial fans ranging in size from 60 mm to 173 mm. The 5915PC AC axial fan models represent a perfect solution for your industrial and factory automation applications. All NMB fans and blowers are RoHS compliant.

Features ▶

- Dual ball bearings
- Metal and plastic impeller available
- High airflow
- Aluminum fan casing
- Thermal/impedance-protected

Benefits ▶

- Low noise
- High quality and reliability
- Long life

Applications ▶

- Factory automation
- Industrial automation
- HVAC
- Lighting
- Tanning beds

Product Specifications ▶

Part Number	Rated Voltage (V)	Frequency (Hz)	Starting Voltage (V)	Current (A)	Input Power (W)	Speed (min ⁻¹)	Maximum Air Flow (CFM)	Maximum Static Pressure (in H ₂ O)	Noise (dB)	Mass (g)
5915PC-12T-B30-A00	115	50	75	0.380	35.0	2700	176.5	0.629	52.0	800
	115	60	75	0.360	32.0	3200	212.0	0.865	56.0	800
5915PC-23T-B30-A00	230	50	145	0.180	35.0	2700	176.5	0.629	52.0	800
	230	60	145	0.190	35.0	3200	212.0	0.865	56.0	800
5915PC-12T-B20-A00	115	50	75	0.200	21.0	2200	141.2	0.393	46.0	800
	115	60	75	0.210	22.0	2600	166.0	0.472	50.0	800
5915PC-23T-B20-A00	230	50	145	0.120	23.0	2200	141.2	0.393	46.0	800
	230	60	145	0.140	26.0	2600	166.0	0.472	50.0	800
5915PC-12T-B10-A00	115	50	75	0.160	16.0	1400	84.7	0.173	35.0	800
	115	60	75	0.190	18.0	1650	102.3	0.243	38.0	800
5915PC-23T-B10-A00	230	50	145	0.090	16.0	1400	84.7	0.169	35.0	800
	230	60	145	0.110	18.0	1650	102.3	0.243	38.0	800

Related Information ▶

Agency Approvals: UL- E89936 Vol. 2, S1/CSA LR65829 1202307/VDE 15073-0012/CE





DC Blowers

NMB's DC and AC axial fans and blowers are designed to solve thermal management challenges. The DC blower Model BG0903 is the solution for your server, PC, and storage cooling needs. NMB's fans and blowers are all RoHS certified.



Features ▶

- Dual ball bearings
- Available in 12V and 24V
- UL, CSA, and VDE approvals
- Auto restart/reverse-polarity protection

Benefits ▶

- Low noise
- Long life
- High quality and reliability

Applications ▶

- Servers
- Storage networks
- PC cooling
- Projectors
- Industrial applications

Product Specifications ▶

Part Number	Rated Voltage (V)	Operating Voltage (V)	Current (A)	Input Power (W)	Speed (min ⁻¹)	Maximum Air Flow (CFM)	Maximum Static Pressure (in H ₂ O)	Noise (dB)	Mass (g)
BG0903-B042-000	12	8-13.8	0.40	4.80	2700	20.50	0.61	47.5	210
BG0903-B043-000	12	6-13.8	0.64	7.68	3200	24.70	0.90	51.5	210
BG0903-B044-000	12	6-12.8	1.03	12.40	3700	28.60	1.40	54.5	210
BG0903-B052-000	24	10-27.6	0.21	5.04	2700	20.50	0.61	47.5	210
BG0903-B053-000	24	10-27.6	0.33	7.92	3200	24.70	0.90	51.5	210
BG0903-B054-000	24	10-25.0	0.49	11.80	3700	28.60	1.40	54.5	210

Related Information ▶

Agency Approvals: UL E89936 Vol. 1, S59/CSA LR65829 1120644/VDE 15073-0039